

Good. Safe. Yellow.

Kronenflex® cutting-off wheels

A 24 R



Klingspor Schleifsysteme GmbH & Co. KG
Hüttenstraße 36 · 35708 Haiger · Germany
Fon +49 (0) 2773 922-0 · Fax +49 (0) 2773 922-186
sales@klingspor.de · www.klingspor.de



A 24 R

Quality

SUPRA

Bond	■ ■ ■ ■ ■ ■ □ □
Aggression	■ ■ ■ ■ □ □ □ □
Service life	■ ■ ■ ■ ■ □ □

Properties

Grain	Aluminium oxide
Quality	Supra
Bond	Medium

Application

Recommended materials	Steel, stainless steel, castings
Machines	Angle grinder

Market segment

- ▶ Maintenance and repair work
- ▶ Steelwork
- ▶ Locksmiths
- ▶ Plant construction

Advantages

- ▶ Optimized combination for use on steel
- ▶ Can be used on stainless steel
- ▶ Good cutting properties
- ▶ Klingspor Kronenflex cutting-off wheels are manufactured in accordance with the oSa and EN12413 standards, this ensures the highest level of user safety

Diameter x Width x Bore in mm	Form	Max. operating speed	Max. RPM	Cat. number
100 x 2,5 x 16		80 m/s	15,300 rpm	13754
115 x 2,5 x 22,23		80 m/s	13,300 rpm	13297
115 x 2,5 x 22,23		80 m/s	13,300 rpm	13466
125 x 2,5 x 22,23		80 m/s	12,200 rpm	13295
125 x 2,5 x 22,23		80 m/s	12,200 rpm	13738
150 x 2,5 x 22,23		80 m/s	10,200 rpm	6667
180 x 3 x 22,23		80 m/s	8,500 rpm	13456
180 x 3 x 22,23		80 m/s	8,500 rpm	13470
180 x 3,5 x 22,23		80 m/s	8,500 rpm	13474
230 x 3 x 22,23		80 m/s	6,600 rpm	13464
230 x 3 x 22,23		80 m/s	6,600 rpm	13478