

Good. Safe. Yellow.

Kronenflex® cutting-off wheels

A 36 TZ



Klingspor Schleifsysteme GmbH & Co. KG
Hüttenstraße 36 · 35708 Haiger · Germany
Fon +49 (0) 2773 922-0 · Fax +49 (0) 2773 922-186
sales@klingspor.de · www.klingspor.de



A 36 TZ

Quality

SPECIAL

Bond	■■■■■■■□
Aggression	■■■■■■■
Service life	■■■■■■□□

Properties

Grain	Aluminium oxide
Quality	Special
Bond	Hard

Application

Recommended materials	Stainless steel, steel
Machines	Angle grinder

Market segment

- ▶ Maintenance and repair work
- ▶ Steelwork
- ▶ Metal fabrication
- ▶ Plant construction

Advantages

- ▶ Particularly suitable for stainless steel and steel processing
- ▶ Very good cutting performance, even with low grinding pressure
- ▶ Klingspor Kronenflex cutting-off wheels are manufactured in accordance with the oSa and EN12413 standards, this ensures the highest level of user safety.

Diameter x Width x Bore in mm	Form	Max. operating speed	Max. RPM	Cat. number
115 x 2 x 22,23	■—■	80 m/s	13,300 rpm	136549
125 x 2 x 22,23	■—■	80 m/s	12,200 rpm	136550
180 x 2 x 22,23	■—■	80 m/s	8,500 rpm	136551
230 x 2 x 22,23	■—■	80 m/s	6,600 rpm	136552